

FASTENERS & TOOLS



RIV720-BATT TOOL FOR RIVETS MAX D.6,4 W/2BATT+CHRG 02,4-06,4

Item No.: 6351800 Multiple quantity: 1

ACCESSORIES SUGGESTS SPARE PARTS

Battery tool equipped with a powerful and reliable brushless motor and long-life battery, the RIV720 makes of easyness and reliability its strong points, offering the customer a value-added solution covering a wide range of applications, for both standard and structural blind rivets from Ø 2.4 up











DESCRIPTION

Battery tool equipped with a powerful and reliable brushless motor and long-life battery, the RIV720 makes of easyness and reliability its strong points, offering the customer a value-added solution covering a wide range of applications, for both standard and structural blind rivets from Ø 2.4 up to Ø 6.4 mm in all major alloys and steels.

Knurled ring nut loosens and tightens by hand.

Cone made of steel for greater strength and durability.

Retractable hook for balancer.

Led light indicates the operation of the tool.

Transparent container for nails easily removable.

Start button robust and well integrated in the structure.

Ergonomic handle made of soft rubber.

Light indicator to light the application area.

Battery led light indicating the charge level.

Composed of:

retention nozzle Ø 4.8 mounted

1 retaining nozzle d.2.4, 3.2, 4.0, 6.4

- 2 batteries
- 1 charger
- 1 wrench 12-17-22-23.5-26
- 1 belt hook
- 2 clamping tubes
- 1 graphite tube 10 gr.

Application

General, tanks, carpentry, different thicknesses. (Standard, sealed, Multigrip rivets)

Building materials, bricks, corrugated panels, insulated roofing. (Fioriv rivets)

Solar panels, roof brackets, variable thicknesses. (Gtreriv, Rivbu, Rivinox rivets)

Plastics, fiberglass, wooden boxes, batteries, cabinets, electrical control panels. (Masriv, Treriv, Goriv rivets)

Number of blind rivets placed with one charge:

(stimated figure with 100% charged battery at room temperature of 25°C)

d. 2.4 Aluminum: 1500/1600d. 3.0/3.2 Aluminum: 1400/1500

d. 3.0/3.2 Steel: 1300/1400

d. 3.0/3.2 Stainless steel: 1200/1300

d. 4.0 Aluminum: 1300/1400

d. 4.0 Steel: 1200/1300

d. 4.0 Stainless steel: 1100/1200d. 4.8 Aluminum: 1200/1300

d. 4.8 Steel: 1100/1200

d. 4.8 Stainless steel: 1000/1100

d. 6.0 Steel: 900/1000

d. 6.0 Stainless steel: 800/900d. 6.4 Aluminum: 1000/1100

d. 6.4 Steel: 900/1000

Packaging

New practical and durable case with a wide range of accessories, including 2 batteries.

The right choice for the professional.

TECHNICAL SPECIFICATIONS

Marchio Statim	Rivit
stroke (mm)	27,0
power (N)	20000
battery	18V / 2.0Ah / 36Wh
charger	100-240V / 50-60Hz
Size of the package (mm)	360x350x130
weight with battery (kg)	1,95